## **Specifications**

| Analysis                                    | System                              | Discrete single line random access multi-test analysis   |
|---|-------------------------------------|--|
|   | Number of test items on board       | 36+3 (ISE) or 24+3(ISE)  |
|   | Throughput                          | 270 tests/hour, 450 tests/hour including ISE, 90tests/hour for HbA1c only                      |
|   | Analysis method                     | End point, Rate, ISE   |
|   | Calibration curve                   | 8 kinds (linear , spline, etc)   |
| Sample                                      | Sample kind                         | Serum, Plasma, Blood cell, Urine, Dialisys, CSF (ISE not available for CSF and Blood cell)     |
|   | Sample container                    | Sample cups , primary tube (5, 7, 10ml)  |
|   | Number of samples on                | Software tray (30 positions for patient sample, and 45 positions for                           |
|   | board                               | standard and blank sample)   |
|   | Sample tray mode<br>(software tray) | Selectable modes for patient sample, calibration and QC  |
|   | Sample dispensing volume            | $2.0 \sim 25.0 \mu l (0.1 \mu l step)$   |
|   | Dilution ratio                      | $0.5 \sim 100 \text{ times}$   |
|   | STAT                                | available during measurement (step between samples by priority)                                |
| Reagent                                     | Reagent tray                        | 36 items or 24 items (removable)   |
|   | Number of bottles on board          | 72 (36 items) or 48 (24 items)   |
|   | Bottle size                         | 36 items : 13, 25, 40 ml   |
|   |                                     | 24 items : 20, 40, 60 ml   |
|   | Reagent dispensing volume           | R1: $140 \sim 300 \mu l(1 \mu l \text{ step})$ , R2: $20 \sim 260 \mu l(1 \mu l \text{ step})$ |
|   | Reagent storage                     | 24 hours cooling   |
|   | Reagent volume check                | Level sensing or count down  |
| Reaction                                    | Cuvette material                    | Plastics (semi-disposable)   |
|   | Reaction volume                     | 140μl ~ 400μl  |
|   | Reaction time                       | approx 10 min. (1st reaction 5 min., 2nd reaction 5 min.)                                      |
|   | Reaction temperature                | 37±0.1℃  |
|   | Optical measurements                | Fixed 13 wavelengths (340 ~ 800nm)   |
|   | Optical source                      | Tungsten halogen lamp  |
|   | Optical range                       | OD 0 ~ 2.5   |
|   | Cuvette washing                     | Auto washing with heated water and 2 kinds of washing solutions                                |
|   | Reaction waste collection           | Reaction waste stored in a dedicated tank  |
|   | Pure water consumption              | Maximum 3.8l /hour   |
| Interface                                   | Operation                           | Personal computer  |
|   | OS                                  | Windows 10   |
|   | Reaction monitor                    | Optical absorbance graphic display   |
|   | Quality control                     | Current, Daily and Cumulative QC. Westgard algorithms  |
|   | Output                              | LAN connection   |
| Option                                      | ISE module                          |  |
|   | Sample barcode reader, Rea          | agent barcode reader   |
| W Specifications are subject to change with |                                     |  |